


D.C. ELECTROSTATIC GENERATORS



Electrostatic Generator - mod. GE-100-1-EASY

The **Electrostatic Generator mod. GE-100-1-EASY** represents a new technological concept and allows excellent flocking quality as well as a higher degree of safety during the working process. It consists of:

- **Electrostatic generator** and this is equipped with an "anti-stalactite" device: in case flock stalactites cause excessive absorption, the generator disconnects itself for a split second, causing the stalactite to fall. This operation is fully automatic and the absorption value after which the unit starts working again can be adjusted.
- **Integrated control panel** allows all the necessary adjustments to be made through the following controls:
 - Low and high tension led signal
 - Tension adjustment and relative display
 - Current adjustment and relative display
 - Alarm

The machine's main features are:

- Highly reliable electronics
- Stabilized supplied tension, which remains constant independently from flocking machine operating conditions
- Adjustable amperage

The generator can be connected to a flocking gun mod. Easy Flock, as in the photo.

TECHNICAL DATA

Dimensions	222 x 245 x 57 mm
Power supply / Maximum output power	230 V/50-60 Hz / 80 Watt
Current adjustable output	0÷1 mA
Max Voltage output	100 KV
Voltage adjustable output	0÷50 KV
Current signal accuracy	1%
Voltage signal accuracy	2%

Member of CISQ Federation



AIGLE